



Specifications

Model Number: W006

Interactive Water Effect: Shall be an arching solid stream effect with 360° directional adjustability.

Housing: 20 gauge deep-drawn type 304 stainless steel with grounding connection and 1" FPT inlet. Supplied with 4, 3/8" x 12" x 2" anchor bolts with two leveling nuts and washers per bolt and wood pour template.

Gaskets: 70 durometer EPDM o-ring.

Construction Cover: Reusable 7" diameter HDPE (high density polyethylene).

Top Plate: 7" diameter slightly domed cast bronze with interchangeable nozzle assembly and UV stabilized, textured elastomeric urethane coating with a UV and chlorine resistant sealer coat.

Top Plate Anchors: Three 1/2" x 5" machined brass with 30° hook bend.

Color: (Specify red, dark blue, light blue, yellow, green, orange, or purple.)

Fasteners: Tamper-resistant 18/8 stainless steel.

Nozzle: Precision machined brass.

Hydraulic Requirements

W006

Height	Throw	GPM	psi
2'	4'	3	2
4'	7'	5	3
6'	10'	7	4

*W006C - Water Conserving Version

Height	Throw	*CGPM	*Cpsi
2'	4'	1	2
4'	7'	2	3
6'	10'	3	4



Aqua Arch™