



Specifications

Model Number: W036C

Interactive Water Effect: Shall be an array of outward arching streams of water.

Housing: 20 gauge deep-drawn type 304 stainless steel with grounding connection and 1" FPT inlet. Supplied with 4, 3/8" x 12" x 2" anchor bolts with two leveling nuts and washers per bolt and wood pour template.

Gaskets: 70 durometer EPDM o-ring.

Construction Cover: Reusable 178mm diameter HDPE (high density polyethylene).

Top Plate: 178mm diameter slightly domed cast bronze with interchangeable nozzle assembly and UV stabilized, textured elastomeric urethane coating with a UV and chlorine resistant sealer coat.

Top Plate Anchors: Three 1/2" x 5" machined brass with 30° hook bend.

Color: (Specify red, dark blue, light blue, yellow, green, orange, or purple.)

Fasteners: Tamper-resistant 18/8 stainless steel.

Nozzles: Six precision machined brass.

Hydraulic Requirements

☐ W036

Height	LPM	psi
600mm	45	2
1200mm	68	3
1800mm	90	4
3000mm	136	6

☒ *W036C - Water Conserving Version

Height	*LPM	*Cpsi
600mm	9.5	2
1200mm	11	3
1800mm	15	4
3000mm	22	6